


Insert small Allen wrench into the bass/treble side vented posts and adjust desired string height for low and high E strings.



Since the installation of stock body thimbles can vary by the thousandth of an inch, you may need to press down on each end of the bridge while loosening to ensure fit.



STEP-BY-STEP GUIDE TO INSTALLING YOUR MASTERY BRIDGE

Congratulations!

You've purchased the finest replacement bridge available for your guitar and the only bridge of its kind. Please take a minute to look over this simple 7 step guide before installation. If you have further questions about how to install your bridge, please contact us at sales@masterybridge.com.

YOUR PACKAGE CONTAINS:

1 Mastery Bridge	1 5/64" Allen wrench (medium)
1 .050" Allen wrench (small)	1 3/32" Allen wrench (large)

Tune instrument to pitch. Fine-tune the action with the four saddle height screws. To adjust the intonation after installment, use the large Allen wrench.



Loosen strings and remove your stock bridge.



THANK YOU FOR CHOOSING MASTERY 

Using the medium size Allen wrench, slightly loosen the mounting post screws.



With the medium size Allen wrench, tighten the mounting post screws.
(Do not over tighten!)



Insert bridge into body thimbles and press down on each end to ensure fit.



Tune instrument to standard pitch.



WARRANTY This Mastery Bridge is warranted to the original consumer purchaser to be free from defects in materials and workmanship under normal installation, use and service for a period of one (1) year from the date of purchase as shown on the purchaser's receipt. This warranty is non-transferrable and does not cover normal wear, nor damage resulting from abuse or any modifications. Shipping expenses are the sole responsibility of the purchaser.